

SterilDisk Probe 10

Temperature data logger from -20°C to 140°C (calibration from 25°C to 140°C), with 10 mm external probe, IP68, in AISI316 L stainless steel, for sterilisation, pasteurisation, cooking processes monitoring. Managed through SPD and TS Manager (compatible with FDA 21 CFR Part 11 regulation) software and the interfaces DiskInterface HS Mini, DiskInterface HS and Multibay. Thanks to its reduced size (36,5 mm diameter) it can be used directly inside packages. Ideal for monitoring where no penetration is needed (no core of the product monitoring) but a quick response time is required; could be used for surface monitoring using the related support. It can be used alone or in combination with other loggers of the same model or different models, also for pressure monitoring. **Battery is user replaceable** and the data logger is **provided with an Accredia (NIST equivalent) traceable certificate** on 6 points.

Other available versions:

- SterilDisk: with internal sensor, for surface monitoring
- SterilDisk Probe: with 3 mm di diameter and 20/50/100/150 mm length probe
- SterilDisk Flexible: with 30 cm flexible probe and 50 mm length rigid probe

There are also other models of high temperature data loggers, for pressure and humidity too.

Main features

- Small size
- With 10 mm probe
- Completely food grade and waterproof
- **All software calculate lethality value (F0, PU, A0 ecc.)**
- User replaceable battery (**software shows battery status**)
- Accredia (NIST equivalent) traceable calibration certificate included
- Available **extended calibration from - 20°C** (order extra calibration points)

Plus

- High accuracy and precision
- Quick response time
- Printed reports compliant with health regulations and ISO (data are not editable in the software)
- Can be fixed to food package and surfaces with the Mounting Base

The system

The system is made up by:

- SterilDisk temperature data logger
- DiskInterface HS Mini or DiskInterface HS or Universal Multibay
- SPD software or TS Manager software (compatible with the FDA 21 CFR Part 11 regulation)



Applications



Sterilisation



Pasteurisation



Food&Beverages



Pharmaceutical



Healthcare



Medical



Laboratories



Validation

Accessories

- SPD
- TS Manager
- DiskInterface HS Mini
- DiskInterface HS
- Universal multibay
- Support for SterilDisk Probe 10
- Fixing base
- Battery kit for SterilDisk, PasteurDisk Can, SterilDisk Can

Technical specifications

Dimensions	17,4 h X 36,5 Ø (mm)
Probe dimensions	10 l X 4 Ø (mm)
Weight	82 gr
Materials	Stainless steel AISI316L, PEEK
Temperature range	-20 °C ÷ +140 °C
Standard calibration points (temperature)	25/50/75/100/125/140°C
Extra calibration points (temperature)	Within the range -20 °C ÷ +140 °C
Temperature resolution	0,01 °C
Temperature accuracy	± 0,2 °C (valida nel range di calibrazione)
Memory (n. of acquisitions)	20.224
Acquisition step	From 1 every second up, with 1 second steps
Protection degree	IP68
Battery life	+1.400.000 acquisizioni ad 1 secondo in continuo (tempo stimato @ 25°C. La vita della batteria è più breve a basse ed alte temperature)
Software&Mobile App	SPD, TS Manager
Accessories	DiskInterface HS Mini, DiskInterface HS, Universal Multibay



Tecnosoft srl
Via Galvani, 4, 20068, Peschiera Borromeo (MI), Italy
T: (+39) 02 2692 2888 - F: (+39) 02 2692 2875
email: info@tecnosoft.eu - web: www.tecnosoft.eu
UNI EN ISO 9001:2008 Certiquality/IQNet N. 17733

